















































## SIZE CHART & STANDARD COLONIAL CONFIGURATIONS

### XO or OX

#### COMMODITY

FLANGE WINDOW WIDTH		26½	37	53⅛	74		
MASONRY OPENING*		27¼	37¾	53⅞	74¾		
INTEGRAL FIN WINDOW WIDTH		25½	36	52⅛	73		
WOOD FRAME OPENING		25¾	36¼	52⅜	73¼		
26	26	25	25¼	 H32	 22	 32	 D22
38⅜	38⅜	37⅜	37⅝	 H33	 23	 33	 D23
50⅝	50⅝	49⅝	49⅞	 H34	 24	 34	 D24
63	63	62	62¼	 H35	 25	 35	 D25

#### MODULAR

FLANGE WINDOW WIDTH		24	36	48	54	60	66	72		
MASONRY OPENING*		24¾	36¾	48¾	54¾	60¾	66¾	72¾		
INTEGRAL FIN WINDOW WIDTH		23	35	47	53	59	65	71		
WOOD FRAME OPENING		23¼	35¼	47¼	53¼	59¼	65¼	71¼		
26	26	25	25¼	 2022	 3022	 4022	 4622	 5022	 5622	 6022
38⅜	38⅜	37	37¼	 2033	 3033	 4033	 4633	 5033	 5633	 6033
50⅝	50⅝	49	49¼	 2043	 3043	 4043	 4643	 5043	 5643	 6043
63	63	62	62¼	 2053	 3053	 4053	 4653	 5053	 5653	 6053
FLANGE WINDOW HEIGHT	MASONRY OPENING*	INTEGRAL FIN WINDOW HEIGHT	WOOD FRAME OPENING	<p><b>Egress availability</b></p> <p> Egress opening is 5.7 square feet or greater</p> <p> Egress opening is between 5.0 and 5.699 square feet</p>						



















\*Note: Openings calculated using 1/8" shim space (maximum 1/4" allowed), 1x bucks and pre-cast sills. If using poured sills add 3/4". Framing dimensions are calculated with drywall butted.

## SIZE CHART & STANDARD COLONIAL CONFIGURATIONS

### XOX

#### COMMODITY

FLANGE WINDOW WIDTH	53 <sup>1</sup> / <sub>8</sub>	74	106 <sup>3</sup> / <sub>8</sub>	111
MASONRY OPENING*	53 <sup>7</sup> / <sub>8</sub>	74 <sup>3</sup> / <sub>4</sub>	107 <sup>1</sup> / <sub>8</sub>	111 <sup>3</sup> / <sub>4</sub>
INTEGRAL FIN WINDOW WIDTH	52 <sup>1</sup> / <sub>8</sub>	73	105 <sup>3</sup> / <sub>8</sub>	110
WOOD FRAME OPENING	52 <sup>3</sup> / <sub>8</sub>	73 <sup>1</sup> / <sub>4</sub>	105 <sup>5</sup> / <sub>8</sub>	110 <sup>1</sup> / <sub>4</sub>

26	26	25	25 <sup>1</sup> / <sub>4</sub>				
				32	D22	D32	T22
38 <sup>3</sup> / <sub>8</sub>	38 <sup>3</sup> / <sub>8</sub>	37 <sup>3</sup> / <sub>8</sub>	37 <sup>5</sup> / <sub>8</sub>				
				33	D23	D33	T23
50 <sup>5</sup> / <sub>8</sub>	50 <sup>5</sup> / <sub>8</sub>	49 <sup>5</sup> / <sub>8</sub>	49 <sup>7</sup> / <sub>8</sub>				
				34	D24	D34	T24
63	63	62	62 <sup>1</sup> / <sub>4</sub>				
				35	D25	D35	T25
FLANGE WINDOW HEIGHT	MASONRY OPENING*	INTEGRAL FIN WINDOW HEIGHT	WOOD FRAME OPENING		Brittany (standard)		Brittany 9-lite (custom)

### DESIGN PRESSURE GUIDE

STYLE	TESTED PRESSURE	WATER-TESTED PRESSURE	TESTED SIZE	TYPE OF TEST
Horizontal Roller	+/-75 psf	11.3 psf	74" x 63"	Miami-Dade Protocols TAS 201, 202, 203

\*Note: Openings calculated using 1/8" shim space (maximum 1/4" allowed), 1x bucks and pre-cast sills. If using poured sills add 3/4". Framing dimensions are calculated with drywall butted.

# SIZE CHART & STANDARD COLONIAL CONFIGURATIONS

## XOX

### MODULAR

FLANGE WINDOW WIDTH	48	60	72	84	96	108
MASONRY OPENING*	48 <sup>3/4</sup>	60 <sup>3/4</sup>	72 <sup>3/4</sup>	84 <sup>3/4</sup>	96 <sup>3/4</sup>	108 <sup>3/4</sup>
INTEGRAL FIN WINDOW WIDTH	47	59	71	83	95	107
WOOD FRAME OPENING	47 <sup>1/4</sup>	59 <sup>1/4</sup>	71 <sup>1/4</sup>	83 <sup>1/4</sup>	95 <sup>1/4</sup>	107 <sup>1/4</sup>

FLANGE WINDOW HEIGHT	26	26	25	25 <sup>1/4</sup>							
	38 <sup>3/8</sup>	38 <sup>3/8</sup>	37 <sup>3/8</sup>	37 <sup>5/8</sup>							
	50 <sup>5/8</sup>	50 <sup>5/8</sup>	49 <sup>5/8</sup>	49 <sup>7/8</sup>							
	63	63	62	62 <sup>1/4</sup>							
	MASONRY OPENING*	INTEGRAL FIN WINDOW HEIGHT	WOOD FRAME OPENING							Brittany (standard)	Brittany 9-lite (custom)

\*Note: Openings calculated using 1/8" shim space (maximum 1/4" allowed), 1x bucks and pre-cast sills. If using poured sills add 3/4". Framing dimensions are calculated with drywall butted.

#### Colonial lites for custom size "XOX" 1/4 1/2 1/4 units are determined by the following:

Window width	44.000" - 60.000"	= 1 lite across per X vent = 2 lites across in fixed
Window width	60.001" - 111.000"	= 2 lites across per X vent = 4 lites across in fixed
Window height	22.125" - 31.999"	= 2 lites down
Window height	32.000" - 42.999"	= 3 lites down
Window height	43.000" - 63.000"	= 4 lites down

#### Colonial lites for custom size "XOX" 1/3 1/3 1/3 units are determined by the following:

Window width	45.125" - 48.233"	= 1 lite across per vent/ fixed
Window width	48.234" - 85.125"	= 2 lites across per vent/ fixed
Window height	22.125" - 31.999"	= 2 lites down
Window height	32.000" - 42.999"	= 3 lites down
Window height	43.000" - 63.000"	= 4 lites down