















































SIZE CHART & STANDARD COLONIAL CONFIGURATIONS

XO or OX

COMMODITY

FLANGE WINDOW WIDTH		26½	37	53⅛	74		
MASONRY OPENING*		27¼	37¾	53⅞	74¾		
INTEGRAL FIN WINDOW WIDTH		25½	36	52⅛	73		
WOOD FRAME OPENING		25¾	36¼	52⅜	73¼		
26	26	25	25¼	 H32	 22	 32	 D22
38⅜	38⅜	37⅜	37⅝	 H33	 23	 33	 D23
50⅝	50⅝	49⅝	49⅞	 H34	 24	 34	 D24
63	63	62	62¼	 H35	 25	 35	 D25

MODULAR

FLANGE WINDOW WIDTH		24	36	48	54	60	66	72		
MASONRY OPENING*		24¾	36¾	48¾	54¾	60¾	66¾	72¾		
INTEGRAL FIN WINDOW WIDTH		23	35	47	53	59	65	71		
WOOD FRAME OPENING		23¼	35¼	47¼	53¼	59¼	65¼	71¼		
26	26	25	25¼	 2022	 3022	 4022	 4622	 5022	 5622	 6022
38⅜	38⅜	37	37¼	 2033	 3033	 4033	 4633	 5033	 5633	 6033
50⅝	50⅝	49	49¼	 2043	 3043	 4043	 4643	 5043	 5643	 6043
63	63	62	62¼	 2053	 3053	 4053	 4653	 5053	 5653	 6053
FLANGE WINDOW HEIGHT	MASONRY OPENING*	INTEGRAL FIN WINDOW HEIGHT	WOOD FRAME OPENING	Egress availability  Egress opening is 5.7 square feet or greater  Egress opening is between 5.0 and 5.699 square feet						



















*Note: Openings calculated using 1/8" shim space (maximum 1/4" allowed), 1x bucks and pre-cast sills. If using poured sills add 3/4". Framing dimensions are calculated with drywall butted.

SIZE CHART & STANDARD COLONIAL CONFIGURATIONS

XOX

COMMODITY

FLANGE WINDOW WIDTH	53 ¹ / ₈	74	106 ³ / ₈	111
MASONRY OPENING*	53 ⁷ / ₈	74 ³ / ₄	107 ¹ / ₈	111 ³ / ₄
INTEGRAL FIN WINDOW WIDTH	52 ¹ / ₈	73	105 ³ / ₈	110
WOOD FRAME OPENING	52 ³ / ₈	73 ¹ / ₄	105 ⁵ / ₈	110 ¹ / ₄

26	26	25	25 ¹ / ₄				
				32	D22	D32	T22
38 ³ / ₈	38 ³ / ₈	37 ³ / ₈	37 ⁵ / ₈				
				33	D23	D33	T23
50 ⁵ / ₈	50 ⁵ / ₈	49 ⁵ / ₈	49 ⁷ / ₈				
				34	D24	D34	T24
63	63	62	62 ¹ / ₄				
				35	D25	D35	T25
FLANGE WINDOW HEIGHT	MASONRY OPENING*	INTEGRAL FIN WINDOW HEIGHT	WOOD FRAME OPENING		Brittany (standard)		Brittany 9-lite (custom)

DESIGN PRESSURE GUIDE

STYLE	TESTED PRESSURE	WATER-TESTED PRESSURE	TESTED SIZE	TYPE OF TEST
Horizontal Roller	+/-75 psf	11.3 psf	74" x 63"	Miami-Dade Protocols TAS 201, 202, 203



























*Note: Openings calculated using 1/8" shim space (maximum 1/4" allowed), 1x bucks and pre-cast sills. If using poured sills add 3/4". Framing dimensions are calculated with drywall butted.

SIZE CHART & STANDARD COLONIAL CONFIGURATIONS

XOX

MODULAR

FLANGE WINDOW WIDTH	48	60	72	84	96	108
MASONRY OPENING*	48 ^{3/4}	60 ^{3/4}	72 ^{3/4}	84 ^{3/4}	96 ^{3/4}	108 ^{3/4}
INTEGRAL FIN WINDOW WIDTH	47	59	71	83	95	107
WOOD FRAME OPENING	47 ^{1/4}	59 ^{1/4}	71 ^{1/4}	83 ^{1/4}	95 ^{1/4}	107 ^{1/4}

FLANGE WINDOW HEIGHT	26	26	25	25 ^{1/4}						
	38 ^{3/8}	38 ^{3/8}	37 ^{3/8}	37 ^{5/8}						
	50 ^{5/8}	50 ^{5/8}	49 ^{5/8}	49 ^{7/8}						
	63	63	62	62 ^{1/4}						
MASONRY OPENING*										
INTEGRAL FIN WINDOW HEIGHT										
WOOD FRAME OPENING										
										
					Brittany (standard)				Brittany 9-lite (custom)	

*Note: Openings calculated using 1/8" shim space (maximum 1/4" allowed), 1x bucks and pre-cast sills. If using poured sills add 3/4". Framing dimensions are calculated with drywall butted.

Colonial lites for custom size "XOX" 1/4 1/2 1/4 units are determined by the following:

Window width	44.000" - 60.000"	= 1 lite across per X vent = 2 lites across in fixed
Window width	60.001" - 111.000"	= 2 lites across per X vent = 4 lites across in fixed
Window height	22.125" - 31.999"	= 2 lites down
Window height	32.000" - 42.999"	= 3 lites down
Window height	43.000" - 63.000"	= 4 lites down

Colonial lites for custom size "XOX" 1/3 1/3 1/3 units are determined by the following:

Window width	45.125" - 48.233"	= 1 lite across per vent/ fixed
Window width	48.234" - 85.125"	= 2 lites across per vent/ fixed
Window height	22.125" - 31.999"	= 2 lites down
Window height	32.000" - 42.999"	= 3 lites down
Window height	43.000" - 63.000"	= 4 lites down