





































































SIZE CHART & STANDARD COLONIAL CONFIGURATIONS

COMMODITY	X						XX	
	FLANGE WINDOW WIDTH	19 1/8	26 1/2	37	37	53 1/8	74	
	MASONRY OPENING*	19 7/8	27 1/4	37 3/4	37 3/4	53 7/8	74 3/4	
	WOOD FRAME OPENING	18 3/8	25 3/4	36 1/4	36 1/4	52 3/8	73 1/4	
26	26	25 1/4	 12	 H32	 22	 22	 32	 D22
38 3/8	38 3/8	37 5/8	 13	 H33	 23	 23	 33	 D23
50 5/8	50 5/8	49 7/8	 14	 H34	 24	 24	 34	 D24
63	63	62 1/4	 15	 H35	 25	 25	 35	 D25
76	76	75 1/4	 16	 H36	 26	 26	 36	 D36
FLANGE WINDOW HEIGHT	MASONRY OPENING*	WOOD FRAME OPENING	 Brittany 9-lite (standard)			 Brittany 6-lite (standard)		 Brittany 9-lite (custom)

**Note: Openings calculated using 1/8" shim space (maximum 1/4" allowed), 1x bucks and pre-cast sills. If using poured sills add 3/4". Framing dimensions are calculated with drywall butted.*

SIZE CHART & STANDARD COLONIAL CONFIGURATIONS

MODULAR

			X				XX		
FLANGE WINDOW WIDTH			24	30	32	36	48	60	72
MASONRY OPENING*			24 ^{3/4}	30 ^{3/4}	32 ^{3/4}	36 ^{3/4}	48 ^{3/4}	60 ^{3/4}	72 ^{3/4}
WOOD FRAME OPENING			23 ^{1/4}	29 ^{1/4}	32 ^{1/4}	35 ^{1/4}	47 ^{1/4}	59 ^{1/4}	71 ^{1/4}
24	24	23 ^{1/4}	 2020	 2620	 2820	 3020	 4020	 5020	 6020
36	36	35 ^{1/4}	 2030	 2630	 2830	 3030	 4030	 5030	 6030
48	48	47 ^{1/4}	 2040	 2640	 2840	 3040	 4040	 5040	 6040
60	60	59 ^{1/4}	 2050	 2650	 2850	 3050	 4050	 5050	 6050
72	72	71 ^{1/4}	 2060	 2660	 2860	 3060	 4060	 5060	 6060
FLANGE WINDOW HEIGHT	MASONRY OPENING*	WOOD FRAME OPENING							

*Note: Openings calculated using 1/8" shim space (maximum 1/4" allowed), 1x bucks and pre-cast sills. If using poured sills add 3/4". Framing dimensions are calculated with drywall butted.

DESIGN PRESSURE GUIDE
















STYLE	TESTED PRESSURE	WATER-TESTED PRESSURE	TESTED SIZE	TYPE OF TEST
Casement	+70/-90 psf	11.5 psf	37" x 63" X 32" x 72" X 74" x 63" XX	Miami-Dade Protocols TAS 201, 202, 203
Casement	+/-55 psf	10.5 psf	37" x 76" X 74" x 76" XX	Miami-Dade Protocols TAS 201, 202, 203

SIZE CHART & STANDARD COLONIAL CONFIGURATIONS

XOX




















COMMODITY

FLANGE WINDOW WIDTH	74	106 ³ / ₈	111
MASONRY OPENING*	74 ³ / ₄	107 ¹ / ₈	111 ³ / ₄
WOOD FRAME OPENING	73 ¹ / ₄	105 ³ / ₈	110 ¹ / ₄

26	26	25 ¹ / ₄	 D22	 D32	 T22
38 ³ / ₈	38 ³ / ₈	37 ⁵ / ₈	 D23	 D33	 T23
50 ⁵ / ₈	50 ⁵ / ₈	49 ⁷ / ₈	 D24	 D34	 T24
63	63	62 ¹ / ₄	 D25	 D35	 T25
76	76	75 ¹ / ₄	 D26	 D36	 T26

MODULAR

FLANGE WINDOW WIDTH	72	84	96	108
MASONRY OPENING*	72 ³ / ₄	84 ³ / ₄	96 ³ / ₄	108 ³ / ₄
WOOD FRAME OPENING	71 ¹ / ₄	83 ¹ / ₄	95 ¹ / ₄	107 ¹ / ₄

24	24	23 ¹ / ₄	 6020	 7020	 8020	 9020
36	36	35 ¹ / ₄	 6030	 7030	 8030	 9030
48	48	47 ¹ / ₄	 6040	 7040	 8040	 9040
60	60	59 ¹ / ₄	 6050	 7050	 8050	 9050
72	72	71 ¹ / ₄	 6060	 7060	 8060	 9060

FLANGE WINDOW HEIGHT
 MASONRY OPENING*
 WOOD FRAME OPENING

DESIGN PRESSURE GUIDE

STYLE	TESTED PRESSURE	WATER-TESTED PRESSURE	TESTED SIZE	TYPE OF TEST
Casement	+70/-90 psf	11.5 psf	120" x 63" XOX	Miami-Dade Protocols TAS 201, 202, 203
Casement	+/-55 psf	10.5 psf	120" x 76" XOX	Miami-Dade Protocols TAS 201, 202, 203

**Note: Openings calculated using 1/8" shim space (maximum 1/4" allowed), 1x bucks and pre-cast sills. If using poured sills add 3/4". Framing dimensions are calculated with drywall butted.*